

选型数据表 Selection data sheet

CISG 系列船用立式单级管道离心泵

CISG series marine vertical single stage pipeline centrifugal pump

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
25-125	2.8	1	20.5	2900	0.52	2.3	HT200/ QT450-10/ 304/316L	NP15A02356																		
	4.0	1	20																							
	5.2	1	18																							
25-125A	2.5	1	17	2900	0.36	2.3			HT200/ QT450-10/ 304/316L	NP15A02356																
	3.6	1	16																							
	4.6	1	14.5																							
25-160	2.8	1	33	2900	1.10	2.3					HT200/ QT450-10/ 304/316L	NP15A02356														
	4.0	1	32																							
	5.2	1	30																							
25-160A	2.6	1	29	2900	0.86	2.3							HT200/ QT450-10/ 304/316L	NP15A02356												
	3.7	1	28																							
	4.9	1	26																							
32-100	3.5	1	14.5	2900	0.33	2.3									HT200/ QT450-10/ 304/316L	NP15A02356										
	4.5	1	12.5																							
	5.3	1	11																							
32-125	3.5	1	22	2900	0.64	2.3											HT200/ QT450-10/ 304/316L	NP15A02356								
	5.0	1	20																							
	6.5	1	18																							
32-125A	3.1	1	17.6	2900	0.45	2.3													HT200/ QT450-10/ 304/316L	NP15A02356						
	4.5	1	16																							
	5.8	1	14.4																							
32-160	4.4	1	28	2900	1.40	2.3															HT200/ QT450-10/ 304/316L	NP15A02356				
	6.3	1	32																							
	8.3	1	30																							
32-160A	2.8	1	27	2900	0.75	2.0																	HT200/ QT450-10/ 304/316L	NP15A02356		
	4.0	1	25																							
	5.2	1	21																							
32-200	3.1	1	50.5	2900	2.40	2.0																			HT200/ QT450-10/ 304/316L	NP15A02356
	4.5	1	50																							
	5.8	1	48																							
32-200A	2.8	1	44.6	2900	1.80	2.0	HT200/ QT450-10/ 304/316L	NP15A02356																		
	4.0	1	44																							
	5.2	1	42.7																							
40-100	4.4	1	13.2	2900	0.40	2.3			HT200/ QT450-10/ 304/316L	NP15A02356																
	6.3	1	12.5																							
	8.3	1	11.3																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
40-100A	3.9	1	10.6	2900	0.36	2.3	HT200/ QT450-10/ 304/316L	NP15A02356																		
	5.6	1	10																							
	7.4	1	9																							
40-125	4.4	1	21	2900	0.80	2.3			HT200/ QT450-10/ 304/316L	NP15A02356																
	6.3	1	20																							
	8.3	1	18																							
40-125A	3.9	1	17.6	2900	0.50	2.3					HT200/ QT450-10/ 304/316L	NP15A02356														
	5.6	1	16																							
	7.4	1	14.4																							
40-160	4.4	1	33	2900	1.40	2.3							HT200/ QT450-10/ 304/316L	NP15A02356												
	6.3	1	32																							
	8.3	1	30																							
40-160A	4.1	1	29	2900	1.10	2.3									HT200/ QT450-10/ 304/316L	NP15A02356										
	5.9	1	28																							
	7.8	1	26.3																							
40-160B	3.8	1	25.5	2900	0.80	2.3											HT200/ QT450-10/ 304/316L	NP15A02356								
	5.5	1	24																							
	7.2	1	22.5																							
40-200	4.4	1	51	2900	2.90	2.3													HT200/ QT450-10/ 304/316L	NP15A02356						
	6.3	1	50																							
	8.3	1	48																							
40-200A	4.1	1	45	2900	2.10	2.3															HT200/ QT450-10/ 304/316L	NP15A02356				
	5.9	1	44																							
	7.8	1	42																							
40-200B	3.7	1	38	2900	1.60	2.3																	HT200/ QT450-10/ 304/316L	NP15A02356		
	5.3	1	36																							
	7.0	1	34.5																							
40-250	4.4	1	82	2900	5.00	2.3																			HT200/ QT450-10/ 304/316L	NP15A02356
	6.3	1	80																							
	8.3	1	74																							
40-250A	4.1	1	72	2900	4.20	2.3	HT200/ QT450-10/ 304/316L	NP15A02356																		
	5.9	1	70																							
	7.8	1	65																							
40-250B	3.8	1	61.5	2900	3.40	2.3			HT200/ QT450-10/ 304/316L	NP15A02356																
	5.5	1	60																							
	7.0	1	56																							
40-100(I)	8.8	1	13.2	2900	0.75	2.3					HT200/ QT450-10/ 304/316L	NP15A02356														
	12.5	1	12.5																							
	16.3	1	11.3																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
40-100(I)A	8.0	1	10.6	2900	0.60	2.3	HT200/ QT450-10/ 304/316L	NP15A02356																		
	11.0	1	10.0																							
	14.5	1	9.0																							
40-125(I)	8.8	1	21.2	2900	1.30	2.3			HT200/ QT450-10/ 304/316L	NP15A02356																
	12.5	1	20.0																							
	16.3	1	17.8																							
40-125(I)A	8.0	1	17	2900	0.90	2.3					HT200/ QT450-10/ 304/316L	NP15A02356														
	11.0	1	16																							
	14.5	1	14																							
40-160(I)	8.8	1	33	2900	2.10	2.3							HT200/ QT450-10/ 304/316L	NP15A02356												
	12.5	1	32																							
	16.3	1	30																							
40-160(I)A	8.2	1	29	2900	1.70	2.3									HT200/ QT450-10/ 304/316L	NP15A02356										
	11.7	1	28																							
	15.2	1	26																							
40-160(I)B	7.3	1	23	2900	1.20	2.3											HT200/ QT450-10/ 304/316L	NP15A02356								
	10.4	1	22																							
	13.5	1	20.5																							
40-200(I)	8.8	1	51.2	2900	3.80	2.3													HT200/ QT450-10/ 304/316L	NP15A02356						
	12.5	1	50																							
	16.3	1	48																							
40-200(I)A	8.3	1	45	2900	3.00	2.3															HT200/ QT450-10/ 304/316L	NP15A02356				
	11.7	1	44																							
	15.3	1	42																							
40-200(I)B	7.5	1	37	2900	2.30	2.3																	HT200/ QT450-10/ 304/316L	NP15A02356		
	10.6	1	38																							
	13.8	1	34																							
40-250(I)	8.8	1	81.2	2900	7.30	2.3																			HT200/ QT450-10/ 304/316L	NP15A02356
	12.5	1	80																							
	16.3	1	77.5																							
40-250(I)A	8.2	1	71	2900	5.70	2.3	HT200/ QT450-10/ 304/316L	NP15A02356																		
	11.6	1	71																							
	15.2	1	68																							
40-250(I)B	7.6	1	61.4	2900	5.00	2.3			HT200/ QT450-10/ 304/316L	NP15A02356																
	10.8	1	60																							
	14	1	58																							
50-100	8.8	1	13.6	2900	0.80	2.3					HT200/ QT450-10/ 304/316L	NP15A02356														
	12.5	1	12.5																							
	16.3	1	11.3																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
500-100A	8	1	11	2900	0.60	2.3	HT200/ QT450-10/ 304/316L	NP15A02356																		
	11	1	10																							
	14.5	1	9																							
50-125	8.8	1	21.5	2900	1.30	2.3			HT200/ QT450-10/ 304/316L	NP15A02356																
	12.5	1	20																							
	16.3	1	17.8																							
50-125A	8	1	17	2900	0.90	2.3					HT200/ QT450-10/ 304/316L	NP15A02356														
	11	1	16																							
	14.5	1	14																							
50-160	8.8	1	33	2900	2.10	2.3							HT200/ QT450-10/ 304/316L	NP15A02356												
	12.5	1	32																							
	16.3	1	30																							
50-160A	8.2	1	29	2900	1.70	2.3									HT200/ QT450-10/ 304/316L	NP15A02356										
	11.7	1	28																							
	15.2	1	26																							
50-160B	7.3	1	23	2900	1.20	2.3											HT200/ QT450-10/ 304/316L	NP15A02356								
	10.4	1	22																							
	13.5	1	20.5																							
50-200	8.8	1	52	2900	4.00	2.3													HT200/ QT450-10/ 304/316L	NP15A02356						
	12.5	1	50																							
	16.3	1	48																							
50-200A	8.3	1	45.8	2900	3.00	2.3															HT200/ QT450-10/ 304/316L	NP15A02356				
	11.7	1	44																							
	15.3	1	42																							
50-200B	7.5	1	37	2900	2.20	2.3																	HT200/ QT450-10/ 304/316L	NP15A02356		
	10.6	1	36																							
	13.8	1	34																							
50-250	8.8	1	82	2900	7.50	2.3																			HT200/ QT450-10/ 304/316L	NP15A02356
	12.5	1	80																							
	16.3	1	77.5																							
50-250A	8.2	1	71.5	2900	5.60	2.3	HT200/ QT450-10/ 304/316L	NP15A02356																		
	11.6	1	70																							
	15.2	1	68																							
50-250B	7.6	1	61.4	2900	5.00	2.3			HT200/ QT450-10/ 304/316L	NP15A02356																
	10.8	1	60																							
	14	1	58																							
50-100(I)	17.5	1	13.7	2900	1.50	2.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	25	1	12.5																							
	32.5	1	10.5																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
50-100(I)A	17.5	1	13.7	2900	1.50	2.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	25	1	12.5																							
	32.5	1	10.5																							
50-125(I)	15.6	1	13	2900	1.10	2.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	22.3	1	10																							
	29	1	8.4																							
50-125(I)A	15.6	1	17	2900	1.80	2.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	22.3	1	16																							
	29	1	13.6																							
50-160(I)	17.5	1	34.4	2900	4.00	2.5							HT200/ QT450-10/ 304/316L	NP15A02356												
	25	1	32																							
	32.5	1	27.5																							
50-160(I)A	16.4	1	30	2900	3.20	2.5									HT200/ QT450-10/ 304/316L	NP15A02356										
	23.4	1	28																							
	30.4	1	24																							
50-160(I)B	15	1	26	2900	2.50	2.5											HT200/ QT450-10/ 304/316L	NP15A02356								
	21.6	1	24																							
	28	1	20.6																							
50-200(I)	17.5	1	52.7	2900	6.00	2.5													HT200/ QT450-10/ 304/316L	NP15A02356						
	25	1	50																							
	32.5	1	45.5																							
50-200(I)A	16.4	1	46.4	2900	5.00	2.5															HT200/ QT450-10/ 304/316L	NP15A02356				
	23.5	1	44																							
	30.5	1	40																							
50-200(I)B	15.2	1	40	2900	4.00	2.5																	HT200/ QT450-10/ 304/316L	NP15A02356		
	21.8	1	38																							
	28.3	1	34.5																							
50-250(I)	17.5	1	82	2900	10.00	2.5																			HT200/ QT450-10/ 304/316L	NP15A02356
	25	1	80																							
	32.5	1	76.5																							
50-250(I)A	16.4	1	71.5	2900	9.40	2.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	23.4	1	70																							
	30.5	1	67																							
50-250(I)B	15	1	61	2900	7.50	2.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	21.6	1	60																							
	28	1	57.4																							
50-315(I)	17.5	1	128	2900	22.00	2.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	25	1	125																							
	32.5	1	122																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
50-315(I)A	16.6	1	115	2900	19.00	2.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	23.7	1	113																							
	31	1	110																							
50-315(I)B	15.7	1	103	2900	15.00	2.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	22.5	1	101																							
	29.2	1	98																							
65-100	17.5	1	13.7	2900	1.50	2.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	25	1	12.5																							
	32.5	1	10.5																							
65-100A	15.6	1	11	2900	1.10	2.5							HT200/ QT450-10/ 304/316L	NP15A02356												
	22	1	10																							
	29	1	8.4																							
65-125	17.5	1	21.5	2900	2.40	2.5									HT200/ QT450-10/ 304/316L	NP15A02356										
	25	1	20																							
	32.5	1	18																							
65-125A	15.6	1	17	2900	1.90	2.5											HT200/ QT450-10/ 304/316L	NP15A02356								
	22.3	1	16																							
	29	1	14.4																							
65-160	17.5	1	34.4	2900	4.00	2.5													HT200/ QT450-10/ 304/316L	NP15A02356						
	25	1	32																							
	32.5	1	27.5																							
65-160A	16.4	1	30	2900	3.20	2.5															HT200/ QT450-10/ 304/316L	NP15A02356				
	23.4	1	28																							
	30.4	1	24																							
65-160B	15	1	26	2900	2.50	2.5																	HT200/ QT450-10/ 304/316L	NP15A02356		
	21.6	1	24																							
	28	1	20.6																							
65-200	17.5	1	52.7	2900	6.00	2.5																			HT200/ QT450-10/ 304/316L	NP15A02356
	25	1	50																							
	32.5	1	45.5																							
65-200A	16.4	1	46.4	2900	5.00	2.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	23.5	1	44																							
	30.5	1	40																							
65-200B	15.2	1	40	2900	4.00	2.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	21.8	1	38																							
	28.3	1	34.5																							
65-250	17.5	1	82	2900	11.00	2.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	25	1	80																							
	32.5	1	76.5																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
65-250A	16.4	1	71.5	2900	8.50	2.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	23.4	1	70																							
	30.5	1	67																							
65-250B	15	1	60	2900	7.50	2.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	21.6	1	61																							
	28	1	57.4																							
65-315	17.5	1	127	2900	22.00	2.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	25	1	125																							
	32.5	1	122																							
65-315A	16.6	1	115	2900	19.60	2.5							HT200/ QT450-10/ 304/316L	NP15A02356												
	23.7	1	113																							
	31	1	110																							
65-315B	15.7	1	103	2900	15.00	2.5									HT200/ QT450-10/ 304/316L	NP15A02356										
	22.5	1	101																							
	29.2	1	98																							
65-100(I)	35	1	13.8	2900	2.80	3.0											HT200/ QT450-10/ 304/316L	NP15A02356								
	50	1	12.5																							
	65	1	10																							
65-100(I)A	31.3	1	11	2900	2.10	3.0													HT200/ QT450-10/ 304/316L	NP15A02356						
	44.7	1	10																							
	58	1	8																							
65-125(I)	35	1	22	2900	4.50	3.0															HT200/ QT450-10/ 304/316L	NP15A02356				
	50	1	20																							
	65	1	17																							
65-125(I)A	31.3	1	17.5	2900	3.30	3.0																	HT200/ QT450-10/ 304/316L	NP15A02356		
	45	1	16																							
	58	1	13.6																							
65-160(I)	35	1	35	2900	7.50	3.0																			HT200/ QT450-10/ 304/316L	NP15A02356
	50	1	32																							
	65	1	28																							
65-160(I)A	32.7	1	62	2900	15.00	3.0	HT200/ QT450-10/ 304/316L	NP15A02356																		
	46.7	1	70																							
	61	1	69																							
65-160(I)B	30.3	1	26	2900	4.70	3.0			HT200/ QT450-10/ 304/316L	NP15A02356																
	43.3	1	24																							
	56.3	1	21																							
60-200(I)	35	1	53.5	2900	12.00	3.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	50	1	50																							
	65	1	46																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing														
60-200(I)A	32.8	1	47	2900	9.20	3.0	HT200/ QT450-10/ 304/316L	NP15A02356														
	47	1	44																			
	61	1	40																			
60-200(I)B	30.5	1	40.6	2900	7.50	3.0			HT200/ QT450-10/ 304/316L	NP15A02356												
	43.5	1	38																			
	56.6	1	33.4																			
65-250(I)	35	1	83	2900	18.00	3.0					HT200/ QT450-10/ 304/316L	NP15A02356										
	50	1	80																			
	65	1	72																			
65-250(I)A	32.5	1	73	2900	15.00	3.0							HT200/ QT450-10/ 304/316L	NP15A02356								
	46.7	1	70																			
	61	1	63																			
65-250(I)B	30	1	62	2900	12.00	3.0									HT200/ QT450-10/ 304/316L	NP15A02356						
	43.3	1	60																			
	56	1	54																			
65-315(I)	35	1	128	2900	31.00	3.0											HT200/ QT450-10/ 304/316L	NP15A02356				
	50	1	125																			
	65	1	121																			
65-315(I)A	32.5	1	112.6	2900	24.00	3.0													HT200/ QT450-10/ 304/316L	NP15A02356		
	46.5	1	110																			
	60.5	1	106.4																			
65-315(I)B	31	1	102.5	2900	22.00	3.0															HT200/ QT450-10/ 304/316L	NP15A02356
	44.5	1	100																			
	58	1	98																			
80-100	35	1	13.8	2900	2.30	3.0	HT200/ QT450-10/ 304/316L	NP15A02356														
	50	1	12.5																			
	65	1	10																			
80-100A	31.3	1	11	2900	1.70	3.0			HT200/ QT450-10/ 304/316L	NP15A02356												
	44.7	1	10																			
	58	1	8																			
80-125	35	1	22	2900	4.50	3.0					HT200/ QT450-10/ 304/316L	NP15A02356										
	50	1	20																			
	65	1	17																			
80-125A	31.3	1	17.5	2900	3.20	3.0							HT200/ QT450-10/ 304/316L	NP15A02356								
	45	1	16																			
	58	1	13.6																			
80-160	35	1	35	2900	6.00	3.0									HT200/ QT450-10/ 304/316L	NP15A02356						
	50	1	32																			
	65	1	28																			

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing												
80-160A	32.7	1	30.6	2900	6.00	3.0	HT200/ QT450-10/ 304/316L	NP15A02356												
	46.7	1	28																	
	61	1	24																	
80-160B	30.3	1	26	2900	4.60	3.0			HT200/ QT450-10/ 304/316L	NP15A02356										
	43.3	1	24																	
	56.3	1	21																	
80-200	35	1	53.5	2900	11.00	3.0					HT200/ QT450-10/ 304/316L	NP15A02356								
	50	1	50																	
	65	1	46																	
80-200A	32.8	1	47	2900	9.20	3.0							HT200/ QT450-10/ 304/316L	NP15A02356						
	47	1	44																	
	61	1	40																	
80-200B	30.5	1	40.6	2900	7.50	3.0									HT200/ QT450-10/ 304/316L	NP15A02356				
	43.5	1	38																	
	56.6	1	33.4																	
80-250	35	1	83	2900	18.00	3.0											HT200/ QT450-10/ 304/316L	NP15A02356		
	50	1	80																	
	65	1	72																	
80-250A	32.5	1	73	2900	15.00	3.0													HT200/ QT450-10/ 304/316L	NP15A02356
	46.7	1	70																	
	61	1	63																	
80-250B	30	1	62	2900	11.60	3.0	HT200/ QT450-10/ 304/316L	NP15A02356												
	43.3	1	60																	
	56	1	54																	
80-315	35	1	128	2900	31.00	3.0			HT200/ QT450-10/ 304/316L	NP15A02356										
	50	1	125																	
	65	1	122																	
80-315A	32.5	1	112.6	2900	24.40	3.0					HT200/ QT450-10/ 304/316L	NP15A02356								
	46.5	1	110																	
	60.5	1	107.4																	
80-315B	31	1	102.5	2900	21.00	3.0							HT200/ QT450-10/ 304/316L	NP15A02356						
	44.5	1	100																	
	58	1	98																	
80-315C	29	1	98	2900	16.10	3.0									HT200/ QT450-10/ 304/316L	NP15A02356				
	41.5	1	85																	
	36	1	83																	
80-350	35	1	146	2900	42.70	3.0											HT200/ QT450-10/ 304/316L	NP15A02356		
	50	1	150																	
	65	1	142																	

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
80-350A	31	1	138.4	2900	37.40	3.0	HT200/ QT450-10/ 304/316L	NP15A02356																		
	44.5	1	142																							
	58	1	134.8																							
80-350B	29	1	131.4	2900	30.80	3.0			HT200/ QT450-10/ 304/316L	NP15A02356																
	41	1	135																							
	53.6	1	127.8																							
80-100(I)	70	1	13.6	2900	4.50	4.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	100	1	12.5																							
	130	1	11																							
80-100(I)A	62.6	1	11	2900	4.20	4.0							HT200/ QT450-10/ 304/316L	NP15A02356												
	89	1	10																							
	116	1	8.8																							
80-125(I)	70	1	23.5	2900	8.50	4.0									HT200/ QT450-10/ 304/316L	NP15A02356										
	100	1	20																							
	130	1	14																							
80-125(I)A	62.6	1	19	2900	6.00	4.0											HT200/ QT450-10/ 304/316L	NP15A02356								
	89	1	16																							
	116	1	11																							
80-160(I)	70	1	36.5	2900	13.00	4.0													HT200/ QT450-10/ 304/316L	NP15A02356						
	100	1	32																							
	130	1	24																							
80-160(I)A	65.4	1	32	2900	11.00	7.5															HT200/ QT450-10/ 304/316L	NP15A02356				
	93.5	1	28																							
	121.6	1	21																							
80-160(I)B	60.6	1	72	2900	8.80	4.5																	HT200/ QT450-10/ 304/316L	NP15A02356		
	86.6	1	24																							
	112.5	1	18																							
80-200(I)	70	1	54	2900	22.00	4.5																			HT200/ QT450-10/ 304/316L	NP15A02356
	100	1	50																							
	130	1	42																							
80-200(I)A	65.4	1	47.5	2900	18.50	4.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	93.5	1	44																							
	121.6	1	37																							
80-200(I)B	61	1	41	2900	15.00	4.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	87	1	38																							
	113	1	32																							
80-250(I)	70	1	87	2900	36.00	4.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	100	1	80																							
	130	1	68																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
80-250(I)A	65.4	1	76	2900	27.39	4.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	93.5	1	70																							
	121.6	1	59.5																							
80-250(I)B	61	1	65	2900	21.95	4.0			HT200/ QT450-10/ 304/316L	NP15A02356																
	87	1	60																							
	113	1	51																							
80-315(I)	70	1	132	2900	52.00	4.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	100	1	125																							
	130	1	114																							
80-315(I)A	66.5	1	119	2900	44.86	4.0							HT200/ QT450-10/ 304/316L	NP15A02356												
	95	1	113																							
	123.6	1	103																							
80-315(I)B	63	1	106.6	2900	38.10	4.0									HT200/ QT450-10/ 304/316L	NP15A02356										
	90	1	101																							
	117	1	92																							
80-315(I)C	58	1	90	2900	29.63	4.0											HT200/ QT450-10/ 304/316L	NP15A02356								
	82	1	85																							
	107	1	76																							
100-100	70	1	13.6	2900	5.20	4.0													HT200/ QT450-10/ 304/316L	NP15A02356						
	100	1	12.5																							
	130	1	11																							
100-100A	62.6	1	11	2900	3.74	4.5															HT200/ QT450-10/ 304/316L	NP15A02356				
	89	1	10																							
	116	1	8.8																							
100-125	70	1	23.5	2900	8.32	4.5																	HT200/ QT450-10/ 304/316L	NP15A02356		
	100	1	20																							
	130	1	14																							
100-125A	62.6	1	19	2900	5.98	4.5																			HT200/ QT450-10/ 304/316L	NP15A02356
	89	1	16																							
	116	1	11																							
100-160	70	1	36.5	2900	13.31	4.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	100	1	32																							
	130	1	24																							
100-160A	65.4	1	32	2900	10.96	4.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	93.5	1	28																							
	121.6	1	21																							
100-160B	60.6	1	27	2900	8.74	4.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	86.6	1	24																							
	112.5	1	18																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
100-200	70	1	54	2900	20.80	4.0	HT200/ QT450-10/ 304/316L	NP15A02356																		
	100	1	50																							
	130	1	42																							
100-200A	65.4	1	47.5	2900	17.22	4.0			HT200/ QT450-10/ 304/316L	NP15A02356																
	93.5	1	44																							
	121.6	1	37																							
100-200B	61	1	41	2900	13.90	4.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	87	1	38																							
	113	1	32																							
100-250	70	1	87	2900	33.28	4.0							HT200/ QT450-10/ 304/316L	NP15A02356												
	100	1	80																							
	130	1	68																							
100-250A	65.4	1	76	2900	27.39	4.0									HT200/ QT450-10/ 304/316L	NP15A02356										
	93.5	1	70																							
	121.6	1	59.5																							
100-250B	61	1	65	2900	21.95	4.0											HT200/ QT450-10/ 304/316L	NP15A02356								
	87	1	60																							
	113	1	51																							
100-315	70	1	132	2900	52.00	4.0													HT200/ QT450-10/ 304/316L	NP15A02356						
	100	1	125																							
	130	1	114																							
100-315A	66.5	1	119	2900	44.87	4.0															HT200/ QT450-10/ 304/316L	NP15A02356				
	95	1	113																							
	123.6	1	103																							
100-315B	63	1	106.6	2900	38.10	4.0																	HT200/ QT450-10/ 304/316L	NP15A02356		
	90	1	101																							
	117	1	92																							
100-315C	58	1	90	2900	29.54	4.0																			HT200/ QT450-10/ 304/316L	NP15A02356
	82	1	85																							
	107	1	76																							
100-350	60	1	153.6	2900	62.40	4.0	HT200/ QT450-10/ 304/316L	NP15A02356																		
	100	1	150																							
	120	1	142																							
100-350A	61	1	145.6	2900	51.95	4.0			HT200/ QT450-10/ 304/316L	NP15A02356																
	87	1	142																							
	113	1	134																							
100-350B	58	1	138.6	2900	46.91	4.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	82	1	135																							
	107	1	127																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
100-100(I)	96	1	14	2900	8.01	4.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	160	1	12.5																							
	192	1	10																							
100-125(I)	96	1	24	2900	12.82	4.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	160	1	20																							
	192	1	14																							
100-125(I)A	84	1	20	2900	9.68	4.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	140	1	17																							
	168	1	12																							
100-160(I)	96	1	36	2900	20.51	5.6							HT200/ QT450-10/ 304/316L	NP15A02356												
	160	1	32																							
	192	1	27																							
100-160(I)A	84	1	32	2900	15.94	5.0									HT200/ QT450-10/ 304/316L	NP15A02356										
	140	1	28																							
	168	1	23.5																							
100-160(I) B	83	1	27	2900	13.51	5.0											HT200/ QT450-10/ 304/316L	NP15A02356								
	138	1	24																							
	166	1	21																							
100-200(I)	96	1	53	2900	32.06	5.2													HT200/ QT450-10/ 304/316L	NP15A02356						
	160	1	50																							
	192	1	45																							
100-200(I)A	84	1	48	2900	13.61	4.5															HT200/ QT450-10/ 304/316L	NP15A02356				
	140	1	45																							
	168	1	40																							
100-200(I)B	60	1	43	2900	17.70	4.5																	HT200/ QT450-10/ 304/316L	NP15A02356		
	100	1	40																							
	120	1	36																							
100-250(I)	96	1	83	2900	51.29	4.8																			HT200/ QT450-10/ 304/316L	NP15A02356
	160	1	80																							
	192	1	72																							
100-250(I)A	84	1	75	2900	42.70	4.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	140	1	75																							
	168	1	65																							
100-250(I)B	60	1	68	2900	27.04	4.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	100	1	65																							
	120	1	58																							
125-100	96	1	13	2900	8.01	4.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	160	1	12.5																							
	192	1	12																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
125-100A	86	1	10.4	2900	5.79	4.0	HT200/ QT450-10/ 304/316L	NP15A02356																		
	143	1	10																							
	172	1	9.6																							
125-125	96	1	22.6	2900	12.82	4.0			HT200/ QT450-10/ 304/316L	NP15A02356																
	160	1	20																							
	192	1	17																							
125-125A	86	1	18	2900	9.28	4.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	143	1	16																							
	172	1	13.6																							
125-160	96	1	36	2900	20.51	4.0							HT200/ QT450-10/ 304/316L	NP15A02356												
	160	1	32																							
	192	1	28																							
125-160A	90	1	31.5	2900	16.95	4.0									HT200/ QT450-10/ 304/316L	NP15A02356										
	150	1	28																							
	180	1	24.5																							
125-160B	83	1	27	2900	13.51	4.0											HT200/ QT450-10/ 304/316L	NP15A02356								
	138	1	24																							
	166	1	21																							
125-200	96	1	55	2900	32.05	5.5													HT200/ QT450-10/ 304/316L	NP15A02356						
	160	1	50																							
	192	1	46																							
125-200A	90	1	48.4	2900	26.64	5.5															HT200/ QT450-10/ 304/316L	NP15A02356				
	150	1	44																							
	180	1	40.5																							
125-200B	83	1	41.3	2900	21.11	5.5																	HT200/ QT450-10/ 304/316L	NP15A02356		
	138	1	37.5																							
	166	1	34.5																							
125-250	96	1	87	2900	51.29	5.5																			HT200/ QT450-10/ 304/316L	NP15A02356
	160	1	80																							
	192	1	73																							
125-250A	90	1	76	2900	42.39	5.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	150	1	70																							
	180	1	84																							
125-250B	83	1	65	2900	33.77	5.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	138	1	60																							
	166	1	55																							
125-315	96	1	133	2900	80.15	5.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	160	1	125																							
	192	1	119																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
125-315A	90	1	117	2900	66.61	5.0	HT200/ QT450-10/ 304/316L	NP15A02356																		
	150	1	110																							
	180	1	104.6																							
125-315B	86	1	106.4	2900	57.99	5.0			HT200/ QT450-10/ 304/316L	NP15A02356																
	143	1	100																							
	172	1	95.2																							
125-315C	80.5	1	96	2900	47.96	5.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	134	1	88																							
	161	1	86																							
150-125	96	1	22.6	2900	12.82	4.0							HT200/ QT450-10/ 304/316L	NP15A02356												
	160	1	20																							
	192	1	17																							
150-125A	90	1	18	2900	9.68	4.0									HT200/ QT450-10/ 304/316L	NP15A02356										
	150	1	16																							
	180	1	13.6																							
150-160	96	1	36	2900	20.52	4.0											HT200/ QT450-10/ 304/316L	NP15A02356								
	160	1	32																							
	192	1	27																							
150-160A	90	1	32	2900	16.95	4.0													HT200/ QT450-10/ 304/316L	NP15A02356						
	150	1	28																							
	180	1	23.5																							
150-160B	84	1	27	2900	13.67	4.0															HT200/ QT450-10/ 304/316L	NP15A02356				
	140	1	24																							
	168	1	21																							
150-200	140	1	13.8	1450	9.87	3.0																	HT200/ QT450-10/ 304/316L	NP15A02356		
	200	1	12.5																							
	260	1	10.6																							
150-200A	125	1	11	1450	7.03	3.0																			HT200/ QT450-10/ 304/316L	NP15A02356
	176	1	10																							
	232.5	1	8.5																							
150-200B	111.7	1	92	1450	5.13	3.0	HT200/ QT450-10/ 304/316L	NP15A02356																		
	160	1	8																							
	207.4	1	6.8																							
150-250	140	1	21.8	1450	15.79	3.0			HT200/ QT450-10/ 304/316L	NP15A02356																
	200	1	20																							
	260	1	17																							
150-250A	129	1	18.5	1450	12.52	3.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	184.4	1	17																							
	240	1	14.4																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
150-250B	117	1	15.2	1450	9.35	3.0	HT200/ QT450-10/ 304/316L	NP15A02356																		
	167	1	14																							
	217.5	1	12																							
150-315	140	1	33.8	1450	25.28	2.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	200	1	32																							
	260	1	28																							
150-315A	131	1	29.5	2900	20.89	3.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	187	1	28																							
	243	1	24.5																							
150-315B	121	1	25	1450	16.59	3.5							HT200/ QT450-10/ 304/316L	NP15A02356												
	173	1	24																							
	225	1	21																							
150-350	96	1	153.6	2900	96.46	5.5									HT200/ QT450-10/ 304/316L	NP15A02356										
	160	1	150																							
	192	1	142.8																							
150-350A	90	1	145.6	2900	85.99	5.5											HT200/ QT450-10/ 304/316L	NP15A02356								
	150	1	142																							
	180	1	134.8																							
150-350B	84	1	138.6	2900	76.87	5.5													HT200/ QT450-10/ 304/316L	NP15A02356						
	140	1	135																							
	168	1	127.8																							
150-400	140	1	53	1450	23.70	3.5															HT200/ QT450-10/ 304/316L	NP15A02356				
	200	1	30																							
	260	1	44																							
150-400A	131	1	40.6	1450	32.73	3.5																	HT200/ QT450-10/ 304/316L	NP15A02356		
	187	1	44																							
	243	1	38.3																							
150-400B	122	1	40	1450	26.38	3.5																			HT200/ QT450-10/ 304/316L	NP15A02356
	174	1	38																							
	226.5	1	33																							
150-400C	112	1	34	1450	20.83	3.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	160	1	32																							
	208	1	28																							
150-250(1)	120	1	87	2900	63.19	4.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	200	1	80																							
	240	1	72																							
150-250(1A)	112	1	76	2900	52.07	4.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	187	1	70																							
	224	1	63																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
150-250(1)B	104	1	65	2900	41.41	4.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	173	1	60																							
	208	1	54																							
150-315(1)	120	1	133	2900	98.73	4.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	200	1	125																							
	240	1	120																							
150-315(1)A	112	1	116	2900	81.83	4.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	187	1	110																							
	224	1	105																							
150-315(1)B	104	1	100	2900	65.67	4.5							HT200/ QT450-10/ 304/316L	NP15A02356												
	173	1	95																							
	208	1	91																							
200-200	140	1	13.8	1450	9.87	3.0									HT200/ QT450-10/ 304/316L	NP15A02356										
	200	1	12.5																							
	260	1	10.6																							
200-200A	175	1	11	1450	7.14	3.0											HT200/ QT450-10/ 304/316L	NP15A02356								
	179	1	10																							
	232.5	1	8.5																							
200-250	140	1	21.8	1450	15.79	3.0													HT200/ QT450-10/ 304/316L	NP15A02356						
	200	1	20																							
	260	1	17																							
200-250A	129	1	18.5	1450	12.47	3.0															HT200/ QT450-10/ 304/316L	NP15A02356				
	184.4	1	17																							
	240	1	14.4																							
200-250B	117	1	15.2	1450	9.38	3.0																	HT200/ QT450-10/ 304/316L	NP15A02356		
	167	1	14																							
	217.5	1	12																							
200-315	140	1	33.8	1450	25.27	3.5																			HT200/ QT450-10/ 304/316L	NP15A02356
	200	1	32																							
	260	1	28																							
200-315A	131	1	29.5	1450	21.05	3.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	189	1	28																							
	243	1	24.5																							
200-315B	121	1	25	1450	12.43	3.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	173	1	24																							
	225	1	21																							
200-400	140	1	53	1450	39.49	3.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	200	1	50																							
	260	1	44																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
200-400A	131	1	46.6	1450	32.77	3.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	187	1	44																							
	243	1	38.3																							
200-400B	122	1	40	1450	26.38	3.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	174	1	38																							
	226.5	1	33																							
200-400C	112	1	34	1450	20.58	3.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	160	1	32																							
	208	1	28																							
200-200(1)	280	1	13.4	1450	18.92	4.0							HT200/ QT450-10/ 304/316L	NP15A02356												
	400	1	12.5																							
	520	1	10.5																							
200-200(1A)	250	1	10.7	1450	13.64	4.0									HT200/ QT450-10/ 304/316L	NP15A02356										
	358	1	10																							
	465	1	8.5																							
200-250(1)	280	1	22.2	1450	30.28	4.0											HT200/ QT450-10/ 304/316L	NP15A02356								
	400	1	20																							
	520	1	14																							
200-500	250	1	18	1450	19.10	4.0													HT200/ QT450-10/ 304/316L	NP15A02356						
	358	1	14																							
	465	1	11.2																							
200-500A	226	1	14.4	1450	16.02	4.0															HT200/ QT450-10/ 304/316L	NP15A02356				
	322	1	13																							
	419	1	7.3																							
200-500B	280	1	36	1450	48.44	4.0																	HT200/ QT450-10/ 304/316L	NP15A02356		
	400	1	32																							
	520	1	26																							
200-315(1A)	262	1	31.5	1450	39.74	4.0																			HT200/ QT450-10/ 304/316L	NP15A02356
	374	1	28																							
	486	1	23																							
200-315(1B)	242	1	27	1450	31.69	4.0	HT200/ QT450-10/ 304/316L	NP15A02356																		
	346	1	24																							
	450	1	19.5																							
200-400(1)	280	1	54.5	1450	75.69	4.0			HT200/ QT450-10/ 304/316L	NP15A02356																
	400	1	50																							
	520	1	39																							
200-400(1A)	262	1	48	1450	62.45	4.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	374	1	44																							
	486	1	34																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
200-400(1)B	242	1	41.4	1450	50.18	5.0	HT200/ QT450-10/ 304/316L	NP15A02356																		
	346	1	38																							
	450	1	29.6																							
200-400(1)C	224	1	34.9	1450	39.19	5.0			HT200/ QT450-10/ 304/316L	NP15A02356																
	320	1	32																							
	416	1	25																							
250-250	350	1	22	1450	40.78	5.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	550	1	20																							
	650	1	16																							
250-250A	300	1	18.3	1450	31.79	5.0							HT200/ QT450-10/ 304/316L	NP15A02356												
	500	1	17																							
	600	1	14																							
250-235	300	1	14	1480	23.33	4.5									HT200/ QT450-10/ 304/316L	NP15A02356										
	500	1	12.5																							
	600	1	11																							
250-300	300	1	22	1480	37.33	4.5											HT200/ QT450-10/ 304/316L	NP15A02356								
	500	1	20																							
	600	1	16																							
250-315	350	1	34	1450	65.25	5.5													HT200/ QT450-10/ 304/316L	NP15A02356						
	550	1	32																							
	650	1	28																							
250-315A	300	1	29.5	1450	52.26	5.5															HT200/ QT450-10/ 304/316L	NP15A02356				
	500	1	28																							
	600	1	24																							
250-315B	260	1	25	1450	40.59	5.5																	HT200/ QT450-10/ 304/316L	NP15A02356		
	450	1	24																							
	520	1	20																							
250-400	300	1	54.5	1480	93.32	4.5																			HT200/ QT450-10/ 304/316L	NP15A02356
	500	1	50																							
	600	1	39																							
250-400A	262	1	46.6	1480	74.42	4.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	450	1	44																							
	521	1	38.3																							
200-500(1)	385	1	87	1480	163.79	5.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	550	1	80																							
	660	1	68																							
200-500(1)A	357	1	76.1	1480	133.08	4.5					HT200/ QT450-10/ 304/316L	NP15A02356														
	510	1	70																							
	612	1	59.5																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing																		
200-500(1)B	329	1	65.2	1480	105.7	4.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	470	1	60																							
	564	1	51																							
300-235	540	1	20.5	1450	47.85	5.0			HT200/ QT450-10/ 304/316L	NP15A02356																
	720	1	18																							
	900	1	15																							
300-235A	450	1	17.2	1450	33.37	5.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	600	1	15																							
	720	1	12.5																							
300-235B	420	1	14.3	1450	25.13	5.0							HT200/ QT450-10/ 304/316L	NP15A02356												
	540	1	12.5																							
	650	1	10.5																							
300-250	540	1	22.5	1450	53.17	6.0									HT200/ QT450-10/ 304/316L	NP15A02356										
	720	1	20																							
	900	1	17																							
300-250A	450	1	19.5	1450	37.82	6.0											HT200/ QT450-10/ 304/316L	NP15A02356								
	600	1	17																							
	720	1	14																							
300-300	540	1	32	1480	74.44	5.0													HT200/ QT450-10/ 304/316L	NP15A02356						
	720	1	28																							
	900	1	23																							
300-300A	450	1	27.5	1480	53.39	5.0															HT200/ QT450-10/ 304/316L	NP15A02356				
	600	1	24																							
	720	1	20																							
300-300B	420	1	24	1480	42.22	5.0																	HT200/ QT450-10/ 304/316L	NP15A02356		
	540	1	21																							
	650	1	17																							
300-315	540	1	35	1480	85.07	4.5																			HT200/ QT450-10/ 304/316L	NP15A02356
	720	1	32																							
	900	1	26																							
300-315A	460	1	31.5	1480	67.38	4.5	HT200/ QT450-10/ 304/316L	NP15A02356																		
	650	1	28																							
	800	1	23.5																							
300-315B	420	1	27	1480	51.68	4.5			HT200/ QT450-10/ 304/316L	NP15A02356																
	580	1	24																							
	700	1	20																							
300-400	540	1	54.5	1480	132.93	5.0					HT200/ QT450-10/ 304/316L	NP15A02356														
	720	1	50																							
	900	1	42																							

型号 Type	流量 Capacity (m ³ /h)	级数	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing												
300-400A	460	1	47	1450	105.89	5.0	HT200/ QT450-10/ 304/316L	NP15A02356												
	650	1	44																	
	800	1	37																	
300-400B	420	1	41	1450	81.82	5.0			HT200/ QT450-10/ 304/316L	NP15A02356										
	580	1	38																	
	700	1	32																	
350-250	600	1	14	980	36.72	4.5					HT200/ QT450-10/ 304/316L	NP15A02356								
	800	1	12.5																	
	960	1	10.5																	
350-250A	800	1	20	980	62.95	4.5							HT200/ QT450-10/ 304/316L	NP15A02356						
	1080	1	16																	
	1350	1	12																	
350-315	600	1	22.5	980	58.76	4.5									HT200/ QT450-10/ 304/316L	NP15A02356				
	800	1	20																	
	960	1	17.5																	
350-315A	600	1	35.5	980	94.02	4.5											HT200/ QT450-10/ 304/316L	NP15A02356		
	800	1	32																	
	960	1	28.5																	
350-315B	600	1	55	980	146.90	4.5													HT200/ QT450-10/ 304/316L	NP15A02356
	800	1	50																	
	960	1	45.5																	
350-400	920	1	23	980	81.67	6.0	HT200/ QT450-10/ 304/316L	NP15A02356												
	1180	1	19																	
	1300	1	16																	
350-400A	950	1	32	980	127.16	6.0			HT200/ QT450-10/ 304/316L	NP15A02356										
	1250	1	28																	
	1500	1	24																	
350-400B	1500	1	16	980	90.71	6.0					HT200/ QT450-10/ 304/316L	NP15A02356								
	1800	1	14																	
	2000	1	12																	