

选型数据表 Selection data sheet

DL 系列船用立式多级离心泵

DL series Marine vertical multistage centrifugal pumps

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL2.4-4	2.4	6	48/67	2900/3500	0.75/0.96	2	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2 (316L)	NP21PPP02823
	2.4	7	56/78	2900/3500	0.87/1.20	2		
	2.4	8	64/89	2900/3500	1.00/1.28	2		
	2.4	9	72/100	2900/3500	1.11/1.44	2		
	2.4	10	80/112	2900/3500	1.24/1.61	2		
	2.4	11	88/123	2900/3500	1.36/1.76	2		
	2.4	12	96/134	2900/3500	1.49/1.92	2		
	2.4	13	104/145	2900/3500	1.61/2.09	2		
	2.4	14	112/156	2900/3500	1.73/2.25	2		
	2.4	15	120/168	2900/3500	1.86/2.41	2		
	2.4	16	128/179	2900/3500	1.98/2.57	2		
	2.4	17	136/190	2900/3500	2.10/2.72	2		
	2.4	18	144/200	2900/3500	2.23/2.89	2		
	2.4	19	152/212	2900/3500	2.35/3.05	2		
	2.4	20	160/224	2900/3500	2.48/3.22	2		
	2.4	21	168/235	2900/3500	2.60/3.38	2		
	2.4	22	176/246	2900/3500	2.72/3.53	2		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL2.4-4	3	6	51/71	2900/3500	1.04/1.33	2	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2 (316L)	NP21PPP02823
	3	7	59.5/83	2900/3500	0.89/1.15	2		
	3	8	68/95	2900/3500	1.19/1.54	2		
	3	9	76.5/107	2900/3500	1.33/1.73	2		
	3	10	85/119	2900/3500	1.48/1.93	2		
	3	11	93.5/130	2900/3500	1.63/2.11	2		
	3	12	102/142	2900/3500	1.78/2.30	2		
	3	13	110/154	2900/3500	1.93/2.50	2		
	3	14	119/166	2900/3500	2.08/2.69	2		
	3	15	127/177	2900/3500	2.23/2.89	2		
	3	16	136/190	2900/3500	2.37/3.08	2		
	3	17	144/201	2900/3500	2.52/3.27	2		
	3	18	153/214	2900/3500	2.67/3.47	2		
	3	19	161/225	2900/3500	2.82/3.65	2		
	3	20	170/238	2900/3500	2.97/3.86	2		
	3	21	178/249	2900/3500	3.12/4.04	2		
	3	22	187/261	2900/3500	3.27/4.23	2		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL2. 4-4	4	6	48/67	2900/3500	1.11/1.44	2	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2 (316L)	NP21PPP02823
	4	7	56/78	2900/3500	1.29/1.67	2		
	4	8	64/89	2900/3500	1.48/1.92	2		
	4	9	72/100	2900/3500	1.67/2.15	2		
	4	10	80/112	2900/3500	1.85/2.41	2		
	4	11	88/123	2900/3500	2.04/2.64	2		
	4	12	96/134	2900/3500	2.22/2.87	2		
	4	13	104/145	2900/3500	2.41/3.13	2		
	4	14	112/156	2900/3500	2.59/3.36	2		
	4	15	120/168	2900/3500	2.78/3.62	2		
	4	16	128/179	2900/3500	2.97/3.85	2		
	4	17	136/190	2900/3500	3.15/4.08	2		
	4	18	144/201	2900/3500	3.34/4.33	2		
	4	19	152/212	2900/3500	3.52/4.57	2		
	4	20	160/224	2900/3500	3.71/4.82	2		
	4	21	168/235	2900/3500	3.89/5.05	2		
	4	22	176/246	2900/3500	4.08/5.28	2		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL2. 4-4	4.8	6	45/63	2900/3500	1.34/1.73	2	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2 (316L)	NP21PPP02823
	4.8	7	52/72	2900/3500	1.56/2.00	2		
	4.8	8	60/84	2900/3500	1.78/2.31	2		
	4.8	9	67.5/94	2900/3500	2.00/2.59	2		
	4.8	10	75/105	2900/3500	2.22/2.89	2		
	4.8	11	82.5/115	2900/3500	2.45/3.17	2		
	4.8	12	90/126	2900/3500	2.67/3.45	2		
	4.8	13	97/135	2900/3500	2.89/3.76	2		
	4.8	14	105/147	2900/3500	3.11/4.03	2		
	4.8	15	112/156	2900/3500	3.34/4.34	2		
	4.8	16	120/168	2900/3500	3.56/4.62	2		
	4.8	17	127/177	2900/3500	3.78/4.90	2		
	4.8	18	135/189	2900/3500	4.01/5.20	2		
	4.8	19	142/198	2900/3500	4.23/5.48	2		
	4.8	20	150/210	2900/3500	4.45/5.79	2		
	4.8	21	157/219	2900/3500	4.67/6.07	2		
	4.8	22	165/231	2900/3500	4.90/6.35	2		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量(NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL6/12	6	2	18/25.9	2830/3470	0.40/0.52	2	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2(316L)	NP21PPP028 23
	6	3	27/37.8	2830/3470	0.60/0.78	2		
	6	4	36/50.4	2840/3470	1.07/1.39	2		
	6	5	45/63	2840/3470	1.33/1.73	2		
	6	6	54/75.6	2840/3470	1.60/2.08	2		
	6	7	63/88.2	2840/3470	1.87/2.43	2		
	6	8	72/100.8	2870/3500	2.14/2.78	2		
	6	9	81/113.4	2870/3500	2.40/3.13	2		
	6	10	90/126	2890/3520	2.67/3.47	2		
	6	11	99/138.6	2890/3520	2.94/3.82	2		
	6	12	108/151.2	2890/3520	3.20/4.17	2		
	6	13	117/163.8	2900/3520	3.47/4.51	2		
	6	14	126/176.4	2900/3520	3.74/4.86	2		
	6	15	135/189	2900/3520	4.01/5.21	2		
	6	16	144/201.6	2900/3520	4.28/5.56	2		
	6	17	153/214.2	2900/3520	4.54/5.90	2		
	6	18	162/226.8	2900/3540	4.81/6.25	2		
	6	19	171/239.4	2900/3540	5.08/6.60	2		
	6	20	180/252	2900/3540	5.35/6.95	2		
	6	21	189/264.6	2900/3540	5.61/7.28	2		
	6	22	198/277.2	2900/3540	5.88/7.62	2		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量(NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL 6/12	8	2	16/22.4	2830/3470	0.68/0.90	2	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2(316L)	NP21PPP028 23
	8	3	24/33.6	2830/3470	1.03/1.32	2		
	8	4	32/44.8	2840/3470	1.37/1.79	2		
	8	5	40/56	2840/3470	1.71/2.22	2		
	8	6	48/67.2	2840/3470	2.05/2.65	2		
	8	7	56/78.2	2840/3470	2.39/3.12	2		
	8	8	64/89.6	2870/3500	2.74/3.59	2		
	8	9	72/100.8	2870/3500	3.08/4.02	2		
	8	10	80/112	2890/3520	3.42/4.44	2		
	8	11	88/123.2	2890/3520	3.76/4.91	2		
	8	12	96/134.4	2890/3520	4.10/5.34	2		
	8	13	104/145.6	2900/3520	4.44/5.77	2		
	8	14	112/156.8	2900/3520	4.79/6.24	2		
	8	15	120/168	2900/3520	5.13/6.67	2		
	8	16	128/179.2	2900/3520	5.47/7.09	2		
	8	17	136/194.6	2900/3520	5.81/7.52	2		
	8	18	144/201.6	2900/3540	6.15/8.03	2		
	8	19	152/212.8	2900/3540	6.50/8.46	2		
	8	20	160/224	2900/3540	6.84/8.89	2		
	8	21	168/235.2	2900/3540	7.18/9.32	2		
	8	22	173/242.2	2900/3540	7.52/9.79	2		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量(NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL6/12	9	2	32/44.8	2840/3490	0.76/1.00	2.1	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2(316L)	NP21PPP028 23
	9	3	48/67.2	2870/3500	1.14/1.48	2.1		
	9	4	64/89.6	2890/3520	1.52/2.00	2.1		
	9	5	80/112	2900/3520	1.90/2.48	2.1		
	9	6	96/134.4	2900/3540	2.29/2.95	2.1		
	9	7	112/156.8	2900/3540	2.67/3.48	2.1		
	9	8	128/179.2	2930/3540	3.05/3.95	2.1		
	9	9	144/201.6	2930/3540	3.43/4.48	2.1		
	9	10	160/224	2930/3540	3.81/4.95	2.1		
	9	11	176/246.4	2930/3540	4.19/5.48	2.1		
	9	12	192/268.8	2930/3540	4.57/5.95	2.1		
	9	13	208/291.2	2930/3550	4.95/6.43	2.1		
	9	14	224/313.6	2930/3550	5.33/6.95	2.1		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀余 量(NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL6/12	10	2	13.6/19	2830/3470	0.84/1.09	2	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2(316L)	NP21PPP028 23
	10	3	20.4/28.6	2830/3470	1.26/1.64	2		
	10	4	27.2/38	2840/3470	1.68/2.18	2		
	10	5	34/47.6	2840/3470	2.10/2.73	2		
	10	6	40.8/57	2840/3470	2.52/3.28	2		
	10	7	47.6/66.6	2840/3470	2.94/3.82	2		
	10	8	54.4/76.1	2870/3500	3.36/4.37	2		
	10	9	61.2/85.7	2870/3500	3.78/4.90	2		
	10	10	68/95.2	2890/3520	4.20/5.46	2		
	10	11	74.5/104.3	2890/3520	4.62/5.98	2		
	10	12	81.6/114.2	2890/3520	5.04/6.55	2		
	10	13	88.4/123.8	2900/3520	5.46/7.10	2		
	10	14	95.2/133.3	2900/3520	5.88/7.65	2		
	10	15	102/142.8	2900/3520	6.30/8.19	2		
	10	16	109/152.6	2900/3520	6.72/8.74	2		
	10	17	115/161	2900/3520	7.14/9.29	2		
	10	18	122/170.8	2900/3540	7.56/9.83	2		
	10	19	129/180.6	2900/3540	7.98/10.38	2		
	10	20	136/190.4	2900/3540	8.40/10.93	2		
	10	21	143/200.2	2900/3540	8.82/11.47	2		
	10	22	150/210	2900/3540	9.24/12.02	2		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head(m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量(NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL6/12	12	2	36/50.4	2870/3500	1.85/2.41	2.3	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2(316L)	NP21PPP028 23
	12	3	54/75.6	2890/3520	2.78/3.62	2.3		
	12	4	72/100.8	2900/3540	3.71/4.82	2.3		
	12	5	90/126	2900/3520	4.64/6.03	2.3		
	12	6	108/151.2	2930/3540	5.57/7.24	2.3		
	12	7	126/176.4	2930/3540	6.49/8.41	2.3		
	12	8	144/201.6	2930/3540	7.42/9.65	2.3		
	12	9	162/226.8	2930/3540	8.35/10.86	2.3		
	12	10	180/252	2930/3550	9.28/12.06	2.3		
	12	11	198/277.2	2930/3550	10.21/13.24	2.3		
	12	12	216/302.4	2930/3550	11.13/14.48	2.3		
	12	13	234/327.6	2940/3560	12.06/15.68	2.3		
	12	14	252/352.8	2940/3560	12.99/16.89	2.3		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL12.5/18	12.5	2	32/44.8	2840/3490	1.93/2.51	2.5	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2(316L)	NP21PPP02823
	12.5	3	48/67.2	2870/3500	2.90/3.77	2.5		
	12.5	4	64/89.6	2890/3520	3.86/5.02	2.5		
	12.5	5	80/112	2900/3520	4.83/6.28	2.5		
	12.5	6	96/134.4	2900/3540	5.80/7.54	2.5		
	12.5	7	112/156.8	2900/3540	6.77/8.80	2.5		
	12.5	8	128/179.2	2930/3540	7.73/10.05	2.5		
	12.5	9	144/201.6	2930/3540	8.70/11.28	2.5		
	12.5	10	160/224	2930/3540	9.67/12.57	2.5		
	12.5	11	176/246.4	2930/3540	10.63/13.79	2.5		
	12.5	12	192/268.8	2930/3540	11.60/15.08	2.5		
	12.5	13	208/291.2	2930/3540	12.57/16.30	2.5		
	12.5	14	224/313.6	2930/3540	13.53/17.60	2.5		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL12.5/18	16	2	27/37.8	2840/3490	2.43/3.61	2.8	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2(316L)	NP21PPP02823
	16	3	40/56	2870/3500	3.64/4.74	2.8		
	16	4	54/75.6	2890/3520	4.86/6.31	2.8		
	16	5	67/93.8	2900/3520	6.07/7.89	2.8		
	16	6	80/112	2900/3540	7.29/9.47	2.8		
	16	7	94/131.6	2900/3540	8.50/11.05	2.8		
	16	8	107/149.8	2930/3540	9.72/12.63	2.8		
	16	9	121/169.4	2930/3540	10.93/14.21	2.8		
	16	10	134/187.6	2930/3540	12.15/15.79	2.8		
	16	11	147/205.8	2930/3540	13.36/17.37	2.8		
	16	12	161/225.4	2930/3540	14.58/18.95	2.8		
	16	13	174/243.6	2930/3540	15.79/20.53	2.8		
	16	14	187/261.8	2930/3540	17.01/22.11	2.8		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL12.5/18	18	2	32/44.8	2870/3500	2.73/3.55	2.8	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2 (316L)	NP21PPP02823
	18	3	48/67.2	2890/3520	4.09/5.32	2.8		
	18	4	64/89.6	2900/3540	5.45/7.09	2.8		
	18	5	80/112	2900/3540	6.82/8.86	2.8		
	18	6	86/120.4	2930/3540	8.18/10.64	2.8		
	18	7	112/156.8	2930/3540	9.54/12.41	2.8		
	18	8	128/179.2	2930/3540	10.90/14.18	2.8		
	18	9	144/201.6	2930/3540	12.27/15.95	2.8		
	18	10	160/224	2930/3550	13.64/17.73	2.8		
	18	11	176/246.4	2930/3550	15.00/19.5	2.8		
	18	12	192/268.8	2930/3550	16.36/21.27	2.8		
	18	13	208/291.2	2940/3560	17.73/23.05	2.8		
	18	14	224/313.6	2940/3560	19.09/24.82	2.8		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL12.5/18	24	2	26/36.4	2870/3500	3.68/4.78	3.6	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2 (316L)	NP21PPP02823
	24	3	39/54.6	2890/3520	5.52/7.17	3.6		
	24	4	52/72.8	2900/3540	7.36/9.56	3.6		
	24	5	65/91	2900/3540	9.20/11.95	3.6		
	24	6	78/109.2	2930/3540	11.03/14.34	3.6		
	24	7	91/127.4	2930/3540	12.87/16.74	3.6		
	24	8	104/145.6	2930/3540	14.71/19.13	3.6		
	24	9	117/163.8	2930/3540	16.55/21.52	3.6		
	24	10	130/182	2930/3550	18.39/23.91	3.6		
	24	11	143/200.2	2930/3550	20.23/26.30	3.6		
	24	12	156/218.4	2930/3550	22.07/28.69	3.6		
	24	13	169/236.6	2940/3560	23.91/31.08	3.6		
	24	14	182/254.8	2940/3560	25.75/33.47	3.6		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head(m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL25/45	25	2	32/44	2870/3500	3.84/4.92	2.3	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2(316L)	NP21PPP02823
	25	3	48/67	2900/3520	5.76/7.44	2.3		
	25	4	64/89	2900/3520	7.68/9.96	2.3		
	25	5	80/112	2930/3540	9.60/12.48	2.3		
	25	6	96/134	2930/3540	11.52/14.88	2.3		
	25	7	112/156	2930/3540	13.44/17.4	2.3		
	25	8	128/179	2930/3540	15.36/19.92	2.3		
	25	9	144/201	2930/3540	17.28/22.44	2.3		
	25	10	160/224	2940/3550	19.20/24.96	2.3		
	25	11	176	2940	21.12	2.3		
	25	12	192	2950	23.04	2.3		
	25	13	208	2950	24.96	2.3		
	25	14	224	2950	26.88	2.3		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head(m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH)r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL25/45	30	2	30/42	2870/3500	4.60/5.89	2.3	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2(316L)	NP21PPP02823
	30	3	45/63	2900/3520	6.90/8.91	2.3		
	30	4	60/84	2900/3520	9.20/8.91	2.3		
	30	5	75/105	2930/3540	11.49/14.94	2.3		
	30	6	90/126	2930/3540	13.79/17.82	2.3		
	30	7	105/147	2930/3540	16.09/20.83	2.3		
	30	8	120/168	2930/3540	18.39/23.85	2.3		
	30	9	135/189	2930/3540	20.69/26.87	2.3		
	30	10	150/210	2940/3550	22.99/29.89	2.3		
	30	11	165	2940	25.29	2.3		
	30	12	180	2950	27.59	2.3		
	30	13	195	2950	29.89	2.3		
	30	14	210	2950	32.18	2.3		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head(m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL25/45	36	2	26/36	2870/3500	5.33/6.83	2.3	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2(316L)	NP21PPP02823
	36	3	39/54	2900/3520	8.00/10.33	2.3		
	36	4	52/72	2900/3520	10.67/13.83	2.3		
	36	5	65/91	2930/3540	13.33/17.33	2.3		
	36	6	78/109	2930/3540	16.00/20.67	2.3		
	36	7	91/127	2930/3540	18.67/24.17	2.3		
	36	8	104/145	2930/3540	21.33/27.67	2.3		
	36	9	117/163	2930/3540	24.00/31.17	2.3		
	36	10	130/182	2940/3550	26.67/34.67	2.3		
	36	11	143	2940	29.33	2.3		
	36	12	156	2950	32.00	2.3		
	36	13	169	2950	34.67	2.3		
	36	14	182	2950	37.33	2.3		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head(m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL25/45	42	2	32/44	2900/3520	6.12/7.84	2.3	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2(316L)	NP21PPP02823
	42	3	48/67	2930/3540	9.18/11.86	2.3		
	42	4	64/89	2930/3540	12.24/15.87	2.3		
	42	5	80/112	2930/3540	15.30/19.89	2.3		
	42	6	96/134	2930/3540	18.36/23.72	2.3		
	42	7	112/156	2940/3550	21.42/27.73	2.3		
	42	8	128/179	2950/3560	24.48/31.75	2.3		
	42	9	144/201	2950/3560	27.54/35.77	2.3		
	42	10	160/224	2950/3560	30.60/39.78	2.3		
	42	11	176	2950	33.66	2.3		
	42	12	192	2950	36.72	2.3		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head(m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL25/45	50	2	27/37	2900/3520	7.17/9.18	2.5	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2(316L)	NP21PPP02823
	50	3	40.5/56	2930/3540	10.75/13.89	2.5		
	50	4	54/75	2930/3540	14.34/18.59	2.5		
	50	5	67.5/94	2930/3540	17.92/23.30	2.5		
	50	6	81/113	2930/3540	21.50/27.78	2.5		
	50	7	94.5/132	2940/3550	25.09/32.48	2.5		
	50	8	108/151	2950/3560	28.67/37.19	2.5		
	50	9	121.5/170	2950/3560	32.26/41.89	2.5		
	50	10	135/189	2950/3560	35.84/46.59	2.5		
	50	11	148.5	2950	39.43	2.5		
	50	12	162	2950	43.01	2.5		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head(m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r(m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL90/120	60	1	17/23	2870/3500	5.29/6.88	2.5	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2 (316L)	NP21PPP02823
	60	2	34/47	2930/3540	10.58/13.76	2.5		
	60	3	51/71	2930/3540	15.87/20.63	2.5		
	60	4	68/95	2930/3540	21.16/27.51	2.5		
	60	5	85/119	2950/3550	26.46/34.39	2.5		
	60	6	102/142	2950/3560	31.74/41.27	2.5		
	60	7	119/166	2950/3560	37.04/48.15	2.5		
	60	8	136/190	2950/3560	42.33/55.03	2.5		
	60	9	153/214	2950/3560	47.62/61.90	2.5		
	60	10	170	2970	52.91	2.5		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head (m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r(m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL90/120	72	1	14/19	2870/3500	6.25/8.13	2.5	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2 (316L)	NP21PPP02823
	72	2	28/39	2930/3540	12.50/6.25	2.5		
	72	3	42/58	2930/3540	18.75/24.38	2.5		
	72	4	56/78	2930/3540	25.00/32.50	2.5		
	72	5	70/98	2950/3550	31.25/40.63	2.5		
	72	6	84/117	2950/3560	37.50/48.75	2.5		
	72	7	98/137	2950/3560	43.75/56.88	2.5		
	72	8	110/154	2950/3560	50.00/65.00	2.5		
	72	9	124/173	2950/3560	56.25/73.13	2.5		
	72	10	140	2970	62.50	2.5		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head(m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r(m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL90/120	90	1	22.5/31.5	2930/3540	7.81/10.16	2.5	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2 (316L)	NP21PPP02823
	90	2	45/63	2930/3540	15.63/20.31	2.5		
	90	3	67.5/94.5	2950/3560	23.44/30.47	2.5		
	90	4	90/126	2950/3560	31.25/40.63	2.5		
	90	5	112.5/157.5	2970/3570	37.90/49.20	2.5		
	90	6	135/189	2970/3570	45.50/59.10	2.5		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head(m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL90/120	108	1	18.5/26	2930/3540	9.10/11.80	2.5	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2 (316L)	NP21PPP02823
	108	2	37/52	2930/3540	18.10/23.60	2.5		
	108	3	55.5/78	2950/3560	27.30/35.50	2.5		
	108	4	74/103	2950/3560	36.40/47.30	2.5		
	108	5	92.5/129	2970/3570	45.50/59.01	2.5		
	108	6	111/155	2970/3570	54.50/59.01	2.5		

型号 Type	流量 Capacity (m ³ /h)	级数 Series	扬程 Head(m)	额定转速 Rated Rev (r/min)	轴功率 Shaft power (kW)	必需汽蚀 余量 (NPSH) r (m)	泵体材质 Pump body material	图纸批准号 Approval No. of drawing
DL90/120	120	1	14/19.5	2930/3540	10.10/13.10	2.5	HT200/ QT450-10/ 06Cr19Ni10 (304) / 022Cr17Ni12Mo2 (316L)	NP21PPP02823
	120	2	28/39	2930/3540	20.20/26.30	2.5		
	120	3	42/58.5	2950/3560	30.30/39.40	2.5		
	120	4	56/78	2950/3560	40.40/52.50	2.5		
	120	5	70/97.5	2970/3570	50.50/65.70	2.5		
	120	6	84/117	2970/3570	60.60/78.80	2.5		